



## Grill Light Bulb Replacement

Part No. BBQ04103060

### **Unplug grill before performing this procedure.**

This procedure applies to Cal Flame grills manufactured since 2010. For replacing bulbs in grills manufactured before 2010, see page 2.

**WARNING:** Never attempt to replace a light bulb when the grill is in use. Serious burns will result.

**WARNING:** Never touch halogen bulbs with your bare fingers. Use a tissue or a small piece of paper to handle bulbs. Oils from your hands will damage halogen bulbs.

#### **Tools required:**

Phillips screwdriver  
Small standard screwdriver

### **Light Removal**

1. Open the grill hood and locate the glass light covers at the back of the grill.
2. Remove the screw at the left or right of the lens.
3. Carefully pull the lens away and out of the light fixture. Set the lens, screw clip, and screw aside.
4. Unscrew the two screws located at the side of the white ceramic light fixture.
5. Using a tissue or small piece of paper, pull the burnt bulb out of the socket.



### **Light Replacement**

1. Using a tissue or small piece of paper, carefully push a new bulb into the socket, making sure both wires on the bulb go into the light socket evenly.
2. Tighten the two screws on the side white ceramic light fixture.
3. Replace the light lens by replacing the screw and screw clip.



## Grill Light Bulb Replacement

Part No. BBQ04103060

### **Unplug grill before performing this procedure.**

This procedure applies to Cal Flame grills manufactured before 2010.

**WARNING:** Never attempt to replace a light bulb when the grill is in use. Serious burns will result.

**WARNING:** Never touch halogen bulbs with your bare fingers. Use a tissue or a small piece of paper to handle bulbs. Oils from your hands will damage halogen bulbs.

**Tools required:**  
Small standard screwdriver

### **Light Removal**

1. Open the grill hood and locate the glass light covers at the back of the grill.
2. Using a small screwdriver, gently pry the light cover away from the housing. *Be extremely careful prying off the light cover. You may damage the light cover as a result.*
3. Unscrew the two screws located at the side of the white ceramic light fixture.
4. Pull the burnt bulb out of the socket.



### **Light Replacement**

1. Using a tissue or small piece of paper, carefully push a new bulb into the socket, making sure both wires on the bulb go into the light socket evenly.
2. Tighten the two screws on the side white ceramic light fixture.
3. Carefully replace the light cover by snapping it in place.